






MINET BENELUX

KEUZE TABEL VOOR SUPER-SCREW VERBINDER

TYPE	SS 35	SS 63 SS 65	SS 80 SS 85	SS 90 SS 95	SS 125	SS 180
Afbeelding						
Banddikte	5 tot 9 mm.	5,1 tot 15 mm.	5,1 tot 20,5 mm.	10 tot 20,5 mm.	8,5 tot 20,5 mm.	8,5 tot 20,5 mm.
Min. trommel Ø	160 mm.	200 – 400 mm.	200 – 400 mm.	300 – 500 mm.	300 – 500 mm.	30 – 500 mm.
Trekkracht (max.)	< 350 N/mm	< 630 N/mm	≤ 800 N/mm	≤ 1.000 N/mm	≤ 1.250 N/mm	≤ 1.800 N/mm
Textiel lagen	2 x 1	2 x 2	2 x 2	2 x 2	2 x 2	2 x 2
Dikte rubber/textiel lagen (per laag)	ca. 3,5 mm.	ca. 4 mm. ca. 6 mm.	ca. 4 mm. ca. 6 mm.	ca. 4 mm. ca. 6 mm.	ca. 6 mm.	ca. 6 mm.
Afmeting verbinder (lengte max. 2.800mm.)	Breedte 60 mm.	Breedte 110 mm.	Breedte 150 mm.	Breedte 268 mm.	Breedte 268 mm.	Breedte 268 mm.
Aantal schroeven	110 stuks (Ø 5 mm.) per meter	196 stuks (Ø 5 mm.) per meter	280 stuks (Ø 5 mm.) per meter	240 stuks (Ø 6,3 mm.) per meter	240 stuks (Ø 6,3 mm.) per meter	240 stuks (Ø 6,3 mm.) per meter